

FILTER HOUSINGS

Our polypropylene filter housings have been designed for maximum performance and durability.

The buttress thread closure provides reliable filter changing and the thick walls and multi-rib design make this a suitable unit for both domestic and industrial applications.

The 10" Clear housing provides an economic alternative for the standard range of cartridges and gives a visual indication of a dirty cartridge.



The caps have bosses for our standard mounting brackets and we supply spanners to facilitate cartridge changing.

Sizes available:

10" Clear
 10" Standard
 20" Standard
 10" Large Diameter (LD)
 20" Large Diameter (LD)
 10" LD Bag Filter
 20" LD Bag Filter

Technical Specification:

Sump & cap: food-grade polypropylene
 O-ring: EPDM (Clear filter: NBR)
 Maximum operating pressure: 8.6bar
 Maximum operating temperature: 52°C
 (Clear filter: 40°C, LD Bag filter: 37°C)
 Minimum operating temperature: 4°C

Please Note: Under certain circumstances, in strong daylight, the Clear housing can promote the growth of algae

We can also supply glass-reinforced housings for temperatures up to 93°C.

Our range of stainless steel single or multi-cartridge housings are used for greater fluid compatibility, high temperatures or higher flow applications.

Water-purifiers.co.uk
 Penstar
 Rhoshill
 Cardigan
 SA43 2TX

Tel: 0845 129 7253
 Fax: 0870 746 8909

info@water-purifiers.co.uk

www.water-purifiers.co.uk